










## Overview of technical details

		NEOREST AC 2.0	NEOREST EW 2.0	WASHLET™ SG 2.0	WASHLET™ RW	WASHLET™ SW	WASHLET™ RX EWATER+	WASHLET™ SX EWATER+	WASHLET™ GL 2.0*	WASHLET™ EK 2.0*
										
WARM WATER SPRAY	Comfort spray flow rate	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0,27 to 0,43l/min		0.27 to 0.43 l/min		0.29 to 0.60 l/min	0.29 to 0.60 l/min
	Soft flow rate	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0,27 to 0,43l/min		0.27 to 0.43 l/min		0.29 to 0.55 l/min	0.29 to 0.55 l/min
	Lady shower flow rate	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0,29 to 0,43l/min		0.29 to 0.43 l/min		0.27 to 0.55 l/min	0.27 to 0.55 l/min
	Continuous-flow water heater	●	●	●	●		●			
	Warm water tank								0.75 l	0.75 l
	Warm water supply	unlimited	unlimited	unlimited	unlimited		unlimited		40 seconds	40 seconds
	Adjustable water temperature	30 to 40 °C	30 to 40 °C	30 to 40 °C	30 to 40 °C		35 to 40 °C		30 to 40 °C	35 to 40 °C
	Water tank reheating time								approx. 15 min	approx. 15 min
COMFORT	Heated seat, individually adjustable temperature	28 to 36 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C		28 to 36 °C		28 to 36 °C	28 to 36 °C
	Deodoriser – Filter system performance	0.16m³/min	0.16m³/min	0.16m³/min	normal 0,09 m³/min, power 0,16 m³/min		normal 0,09 m³/min, power 0,16 m³/min		0.16m³/min	0.16m³/min
	Dryer with adjustable temperature	35 to 55 °C approx. 0.29m³/min	35 to 55 °C approx. 0.29m³/min	35 to 55 °C approx. 0.29m³/min	37 to 55 °C approx. 0,29 m³/min		37 to 55 °C approx. 0,29 m³/min		37 to 55 °C approx. 0.27m³/min	37 to 55 °C approx. 0.27m³/min
CONNECTIONS / PIPES	Power outlet required	●	●	●	●		●		●	●
	Water connection pressure	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10Bar		1 to 10bar		1 to 10 bar	1 to 10 bar
	Power input	1,289–1,527 W	1,289–1,527 W	1,290–1,528 W	1,455–1,468 W		1,437–1,459 W		276–321 W	276–321 W
	Connection limits	220–240 V/50 Hz	220–240 V/50 Hz	220–240 V/50 Hz	220–240 V/50 Hz		220–240 V/50 Hz		220–240 V/50 Hz	220–240 V/50 Hz
ECO	EN 1717 (Drinking water safety)	●	●	●	●		●		●	●

\* with side or hidden connections

## WC-/WASHLET™ combinations

		NEOREST AC 2.0	NEOREST EW 2.0	WASHLET™ SG 2.0	WASHLET™ RW	WASHLET™ SW	WASHLET™ RX EWATER+	WASHLET™ SX EWATER+	WASHLET™ GL 2.0		WASHLET™ EK 2.0	
									with hidden connections	with side connections	with hidden connections	with side connections
TOILET	WC NEOREST AC 2.0 with Zirconium coating	●										
	WC NEOREST EW		●									
	WC SG			●								
	WC RP				● CW542EY		● CW542EY					
	WC SP					● CW522EY		● CW522EY				
	WC MH								● CW162YH	●	● CW162YH	●
	WC NC									●		●
	WC ES									●		●